



Polished Porcelain Sealer

Water based Impregnating Sealer

Interior & exterior use

For all types of polished porcelain.

Natural finish water based impregnating sealer. Provides minimal change to the original appearance. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe.

Directions for use

Preparation:

Ensure surface to be treated is completely clean, dry and free from factory nano-wax dirt, grime, cement and grout. Clean and scrub surfaces thoroughly prior to application using Stone & Tile Intensive Cleaner diluted 1:4 with water and scrub surface with a white emulsifying pad. Rinse well to remove residues and leave to dry.

Application:

Shake bottle before use. Apply liberally and evenly using a sealant applicator pad, lint free cloth, lamb's wool applicator or sponge. Leave surfaces to dry. Remove any residual sealer if still visible after one hour by buffing with a micro fibre cloth or buffing machine.

On vertical surfaces apply from the bottom up.

Coverage: M² per coat

	1 LTR	5 LTR	25 LTR
Polished surfaces	30m ²	150m ²	N/A

Aftercare

Routinely sweep and wash the floor. Clean walls, floors and work surfaces with Eco Pro Tec Natural Stone & after Care Cleaner.

Storage information

Store in a cool, dry, frost-free environment. Store locked up.

Shelf Life – Up to 2 years for un-opened containers.

Other

Dried on over applied sealer can be removed by buffing with micro fibre cloth or rotary machine and buffing pad. If dried on residues are left too long and difficult to buff away; apply a little soapy water and gently scrub with a white emulsifying pad, rinse and leave to dry

Empty containers are recyclable. Active ingredients are water soluble and inert once cured.

Turn off under-floor heating prior to sealing. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces. On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated.

Do not use in temperatures under 5°C or over 25°C. Clean application tools and brushes with water after use.

Health, Safety & Environmental

Attention:

Keep out of reach of children.

Dispose of contents/container to a licensed waste centre in accordance with local /regional/national/international regulations.

Contains mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)(55965-84-9). May produce an allergic reaction Safety data sheet available on request



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

