



**Natural Finish Stone Sealer**

**Water based Impregnating Sealer**

**Interior & exterior use**

For all types of natural and artificial stone, quarry, brick, concrete & paving. Honed, rough cut and polished surfaces.

A natural finish water based impregnating sealer. Minimal change to surface character. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe. Helps reduce efflorescence.

**Directions for use**

**Preparation:**

Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. If necessary, first wash surfaces with a dilute solution of Stone & Tile Intensive Cleaner 1:10 and white pad. Rinse well to remove residues and leave to dry (24hrs).

**Rough cut, tumbled, textured or riven surfaces** Shake bottle before use. Apply generously and evenly using foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is fully saturated.

**Honed, smooth and polished surfaces** Shake bottle before use. Apply liberally and evenly using a sealant applicator pad, lint free cloth, lamb's wool applicator or sponge. Leave surfaces to dry. Remove any residual sealer if still visible after one hour.

**Do not use a sprayer to apply due to risk of aspiration.**

On vertical surfaces apply from the bottom up.

**Coverage: M<sup>2</sup> per coat**

	1 LTR	5 LTR	25 LTR
Lower porosity surfaces	15m <sup>2</sup>	75m <sup>2</sup>	375m <sup>2</sup>
Higher porosity surfaces	7.5m <sup>2</sup>	37.5m <sup>2</sup>	187.5m <sup>2</sup>
Polished surfaces	30m <sup>2</sup>	150m <sup>2</sup>	750m <sup>2</sup>

**Aftercare**

Routinely sweep and wash the floor. Clean walls, floors and work surfaces with Eco Pro Tec Natural Stone & after Care Cleaner.

**Storage information**

Store in a cool, dry, frost-free environment. Store locked up.

Shelf Life – Up to 2 years for un-opened containers.

**Other**

Dried on over applied sealer can be removed by buffing with micro fibre cloth or rotary machine with buffing pad. If dried on residues are left too long and difficult to buff away; apply a little soapy water and gently scrub with a white emulsifying pad, rinse and leave to dry.

Empty containers are recyclable. Active ingredients are water soluble and inert once cured.

Turn off under-floor heating prior to sealing. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces. On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated.

Do not use in temperatures under 5°C or over 25°C. Clean application tools and brushes with water after use.

**Health, Safety & Environmental**

**Harmful if swallowed, in contact with skin or if inhaled.**

**Harmful to aquatic life with long lasting effects**

Keep out of reach of children. Do not breathe vapours/spray.

Avoid release into the environment. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell. Dispose of contents/container to hazardous or special waste collection point.



**WARNING**



*This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area*

